

Page 1 of 7

TECHNICAL CONSTRUCTION FILE			
Report Reference No:	TCGD20031722712		
Tested by (+ signature):	Jessica Meng		
Approved by (+ signature):	Kevin Shi		
Date of issue:	March 16, 2020		
Testing Laboratory:	Shanghai Global Testing Services Co., Ltd.		
Address:	Floor 2nd, Building D-1, No. 128, Shenfu Road, Minhang District, Shanghai, China.		
Testing procedure:	TL[X] TMP[] WMT[]		
Applicant's name:	Angel Leather Technology Co.,Ltd.		
Address:	HongJin Road, Wusha Industrial Zone, wusha Village, HongMei Town, DongGuan City, Guang Dong Province, China.		
Test specification:			
Standard:	EN 149:2001+A1:2009		
Type of Test:	PST[] Registration (type test) [X]		
Non-standard test method:	N/A		
Manufacturer:	Angel Leather Technology Co.,Ltd.		
Adress:	HongJin Road, Wusha Industrial Zone, wusha Village, HongMei Town, DongGuan City, Guang Dong Province, China.		
Product name:	Face Mask		
Model No:	AJ-XY-SLSX-002		



Page 2 of 7

Report No. TCGD20031722712

Possible test case verdicts:	
- test case does not apply to the test object:	N/A
- test object does meet the requirement:	P(Pass)
- test object does not meet the requirement:	F(Fail)
Testing	
Date of receipt of test item:	March 06, 2020
Date (s) of performance of tests	March 06, 2020 to March 16, 2020

General remarks:

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

"(see Enclosure #)" refers to additional information appended to the report.

"(see appended table)" refers to a table appended to the report.

Throughout this report a comma (point) is used as the decimal separator.



Page 3 of 7

TEST CONDUCTED:

Respiratory protective devices — Filtering half masks to protect against particles — Requirements, testing, marking

(EN 149:2001 +A1:2009)

Test Property	Test Method	Test Principle / Requirements	The Result
7. Requirements			
General	EN149	In all tests all test samples shall meet	-
	Clause 7.1	the requirements.	
Nominal values and	EN149	Unless otherwise specified, the	Pass
tolerances	Clause 7.2	values stated in this European	
		Standard are expressed as nominal	
		values. Except for temperature limits,	
		values which are not stated as	
		maxima or minima shall be subject to	
		a tolerance of \pm 5 %. Unless	
		otherwise specified, the ambient	
		temperature for testing shall be (16 -	
		32) ° C, and the temperature limits	
		shall be subject to an accuracy of \pm	
		1 ° C.	
Visual inspection	EN149	The visual inspection shall also	Pass
	Clause 7.3	include the marking and the	
		information supplied by the	
		manufacturer.	
Packaging	EN149	Particle filtering half masks shall be	Pass
	Clause 7.4	offered for sale packaged in such a	
		way that they are protected against	
		mechanical damage and	
		contamination before use.	
Material	EN149	Materials used shall be suitable to	Pass
	Clause 7.5	withstand handling and wear over the	
		period for which the particle	
		filtering half mask is designed to be	
		used.	
		After undergoing the conditioning	
		described in 8.3.1 none of the particle	
		filtering half masks shall have	
		suffered mechanical failure of the	



Page 4 of 7

Report No. TCGD20031722712

Test Property	Test Method	Test Principle / Requirements	The Result
		facepiece or straps.	
		Three particle filtering half masks	
		shall be tested.	
		When conditioned in accordance with	
		8.3.1 and 8.3.2 the particle filtering	
		half mask shall not collapse.	
		Any material from the filter media	
		released by the air flow through the	
		filter shall not constitute a hazard	
		or nuisance for the wearer.	
Cleaning and	EN149	If the particle filtering half mask is	Pass
disinfecting	Clause 7.5	designed to be re-usable, the	
		materials used shall withstand the	
		cleaning and disinfecting agents and	
		procedures to be specified by the	
		manufacturer	
Practical	EN149	The particle filtering half mask shall	Pass
performance	Clause 7.7	undergo practical performance tests	
		under realistic conditions.	
		These general tests serve the	
		purpose of checking the equipment	
		for imperfections that cannot be	
		determined by the tests described	
		elsewhere in this standard.	
Finish of parts	EN149	Parts of the device likely to come into	Pass
	Clause 7.8	contact with the wearer shall have no	
		sharp edges or burrs.	
7.9 Leakage			
Total inward leakage	EN149	The laboratory tests shall indicate	Pass
	Clause 7.9.1	that the particle filtering half mask	
		can be used by the wearer to protect	
		with high probability against the	
		potential hazard to be expected.	
		The total inward leakage consists of	
		three components: face seal leakage,	
		exhalation valve leakage (if	
		exhalation valve fitted) and filter	
		penetration.	
		·	



Page 5 of 7

Report No. TCGD20031722712

Test Property	Test Method	Test Principle / Requirements	The Result
Penetration of filter	EN149	The penetration of the filter of the	Pass
material	Clause 7.9.2	particle filtering half mask shall meet	
		the requirements of Table 1.	
Compatibility with	EN149	Materials that may come into contact	Pass
skin	Clause 7.10	with the wearer's skin shall not be	
		known to be likely to cause	
		irritation or any other adverse effect	
		to health.	
Flammability	EN149	The material used shall not present a	<5s
	Clause 7.11	danger for the wearer and shall not	Pass
		be of highly flammable nature.	
		When tested, the particle filtering half	
		mask shall not burn or not to continue	
		to burn for more than 5 s	
		after removal from the flame.	
Carbon dioxide	EN149	The carbon dioxide content of the	Pass
content of the	Clause 7.12	inhalation air (dead space) shall not	
inhalation air		exceed an average of 1,0 % (by	
		volume).	
Head harness	EN149	The head harness shall be designed	N/A
	Clause 7.13	so that the particle filtering half mask	
		can be donned and removed	
		easily.	
		The head harness shall be adjustable	
		or self-adjusting and shall be	
		sufficiently robust to hold the particle	
		filtering half mask firmly in position	
		and be capable of maintaining total	
		inward leakage requirements for	
		the device.	
Field of vision	EN149	The field of vision is acceptable if	Pass
	Clause 7.14	determined so in practical	
		performance tests.	
Exhalation valve(s)	EN149	A particle filtering half mask may	N/A
	Clause 7.15	have one or more exhalation	
		valve(s), which shall function	
		correctly in	
		all orientations.	

Floor 2nd, Building D-1, No. 128, Shenfu Road, Minhang District, Shanghai, China.

Tel: (86-21) 3363 7866 Fax: (86-21) 3363 7858 E-mail: info@gts-lab.com Web Site: http://www.gts-lab.com



Page 6 of 7

Report No. TCGD20031722712

Test Property	Test Method	Test Principle / Requirements	The Result
Breathing resistance	EN149	The breathing resistances apply to	Pass
	Clause 7.16	valved and valveless particle filtering	
		half masks and shall meet the	
		requirements of Table 2.	
7.17 Clogging			
General	EN149	For re-usable devices the test is	N/A
	Clause 7.17.1	mandatory.	

Sample Photo:





Page 7 of 7



*****End of Report*****